1/1

## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2000-230098

(43)Date of publication of

22.08.2000

application:

(51)Int.Cl.

C08L 29/04

C08L101/02

(21)Application

(22)Date of filing:

11-035544

(71)

KURARAY CO LTD

number:

15.02.1999

(72)Inventor:

Applicant:

TANIMOTO SEIJI

**FUJIWARA NAOKI** 

## (54) AQUEOUS EMULSION COMPOSITION

## (57) Abstract:

PROBLEM TO BE SOLVED: To obtain an aqueous emulsion composition excellent in viscosity stability upon being left standing and water-resistant adhesiveness and useful as e.g. a wood adhesive by mixing an amino-containing water-based resin with an aqueous emulsion in which the dispersoid is a polymer having units derived from an unsaturated monomer selected from among ethylenically unsaturated monomers and diene monomers and the dispersant is a vinyl alcohol polymer.

SOLUTION: The vinyl alcohol polymer as the dispersant of the aqueous emulsion is desirably a vinyl alcohol polymer having a degree of saponification of at least 95 mol % and/or a polyvinyl alcohol polymer containing 1-15 mol % ethylene units in the molecule and having a degree of saponification of at least 95 mol %. The polymer as the dispersoid is exemplified by polyvinyl acetate. The amino-containing water-based resin is exemplified by a vinylamine polymer, an allylamine polymer, an arnino-containing acrylic emulsion, or an amino-containing water-based acrylic resin.